

Clear Runway Within Minutes

Ideal for single runway airports

Standard Features:

- Move disabled aircraft quickly and carefully
- Reduce damage to aircraft
- Fits over 140 aircraft under 40,000 lbs
- Simple operation, can be managed by one (1) person
- Durable, heavy structural steel construction
- 33 in (83.8 cm) maximum aircraft wheel width
- 42° maximum turning angle
- Front and rear wheels pivot allowing dolly to be lowered for ease of loading
- Finish: Durable Powder Coat Tronair Blue
- Solid rubber tires
- Four (4) steel skid wheels for final positioning
- Self-leveling foot pads accommodate uneven towing surfaces
- Front and rear hydraulic systems
- Hand pumps require 35 lb. handle force to actuate total hydraulic cylinder movement
- Heavy duty chain pullers easily cinch aircraft tires



Specifications:

Model Number	Load Capacity lb (kg)	Max Towing Speed mph (kph)	Length in (cm)	Width in (cm)	Height in (cm)	Weight lb (kg)
02-4951-0100.....	16,000 (7,257)	5 (8)	177 (449.6).....	60 (152.4).....	20 (50.8).....	1,200 (544.3)

www.tronair.com

Tronair • Email: sales@tronair.com • Phone: 419-866-6301 or 800-426-6301 • Fax: 419-867-0634

Asia Sales Offices: China - Email: tronairchina@tronair.com • Phone: 86-592-5560735 • Fax: 86-592-5563132

Asia/Australia - Email: tronairasia@tronair.com • Phone: 66-2665-6511 • Fax: 66-2204-1858

Europe, Middle East & Africa Sales Office • Email: saleseurope@tronair.com • Phone: 44-0-113-245-3300 • Fax: 44-0-113-322-0436

TR021210